Алматы (7273)495-231 Ангарск (3955)60-70-56 Архангельск (8182)63-90-72 Астрахань (8512)99-46-04 Барнаул (3852)73-04-60 Белгород (4722)40-23-64 Благовещенск (4162)22-76-07 Брянск (4832)59-03-52 Владивоеток (423)249-28-31 Владикавказ (8672)28-90-48 Владимир (4922)49-43-18 Волгоград (844)278-03-48 Вологара (8172)26-41-59 Воронеж (473)204-51-73 Екатеринбург (343)384-55-89 Иваново (4932)77-34-06 Ижевск (3412)26-03-58 Иркутск (395)279-98-46 Казань (843)206-01-48 Калининград (4012)72-03-81 Калуга (4842)92-23-67 Кемерово (3842)65-04-62 Киров (8322)68-02-04 Кострома (4966)23-41-49 Кострома (4942)77-07-48 Краснодар (861)203-40-90 Красноярск (391)204-63-61 Курск (4712)77-13-04 Курсан (3522)50-90-47 Липецк (4742)52-20-81

Россия +7(495)268-04-70

Model

Магнитогорск (3519)55-03-13 Москва (495)268-04-70 Мурманск (8152)59-64-93 Набережные Челны (8552)20-53-41 Нижний Новгород (831)429-08-12 Новокузнецк (3843)20-46-81 Ноябрьск (3843)20-46-81 Ноябрьск (3843)22-786-73 Омск (3812)21-46-40 Орел (4862)44-53-42 Оренбург (3532)37-68-04 Пенза (8412)22-31-16 Петрозаводск (8142)55-98-37 Псков (8112)59-10-37 Пермь (342)205-81-47 Казахстан +7(712)727-132 Ростов-на-Дону (863) 308-18-15 Рязань (4912) 46-61-64 Самара (846) 206-03-16 Санкт-Петербург (812) 309-46-40 Саратов (845) 249-38-78 Севастополь (8692) 22-31-93 Саранск (8342) 22-96-24 Симферополь (8652) 20-65-13 Симск (4812) 29-41-54 Сочи (862) 225-72-31 Ставрополь (8652) 20-65-13 Сургут (3462) 77-98-35 Сыктывкар (8212) 25-95-17 Тамбов (4752) 50-40-97 Тверь (4822) 63-31-35

9

20

3.

9

40

新生物花

Тольятти (8482)63-91-07 Томск (3822)98-41-53 Тула (4872)33-79-87 Тюмень (3452)66-21-18 Ульяновск (8422)24-23-59 Улан-Удэ (3012)59-97-51 Уфа (347)229-48-12 Хабаровск (4212)92-98-04 Чебоксары (8352)28-53-07 Челябинск (351)202-03-61 Череповец (8202)49-02-64 Чита (3022)38-34-83 Якутск (4112)23-90-97 Яроспавль (4852)69-52-93

MENU/ESC

ENTER

RANGE

MARK

FUNC

GAIA

Киргизия +996(312)96-26-47

5.7" Color LCD FISH FINDER

FURUNA

G:AF

AUTO_R

\/-

https://furuno.nt-rt.ru || fon@nt-rt.ru

High resolution fish echoes with RezBoost™ technology!





FCV-628 uses revolutionary new RezBoost™ in resolution and target separation, utilizing

NEW

RezBoost

Model

Fish Finder technology just took a big leap with RezBoost™!

18.

RezBo

RezBoost[™]

RezBoost[™] is a revolutionary new signal processing technology developed by FURUNO that improves resolution and target separation when using conventional narrowband transducers. Spot individual game fish surrounding bait balls, as well as fish close to the seabed. With RezBoost[™], not only can you expect higher resolution and crisper visuals, but also improvements in the ACCU-FISH[™] function.

With RezBoost[™] the capabilities of conventional narrowband transducers can be dramatically improved. Compared to conventional signal processing techniques (FDF), a RezBoost[™] fish finder produces an image that is up to 8 times^{*1} clearer.

A TruEcho CHIRP[™] fish finder (requires a special transducer) produces an image that is up to 10 times^{*1} clearer when compared with FDF. What can be done with a conventional narrowband transducer, just like the one you might have installed on your vessel, is truly impressive^{*2}.

*1 RezBoost™ performance may vary depending on depth, range and signal frequency used.
*2 The Enhanced mode of RezBoost™ requires a RezBoost™ capable thru-hull or transom mount transducer.

5.7" Color LCD FISH FINDER

FCV-628

technology, providing an incredible boost a compact narrowband transducer

With RezBoost[™] technology, the resolution is increased, leading to sharper and more defined echoes. Thanks to this increase in resolution, the accuracy of the ACCU-FISH[™] function is also improved. ACCU-FISH[™] is very useful when you need to determine fish size, but also has the added benefit of making fish echoes more visible when viewed from a distance. With ACCU-FISH[™] you can spot individual fish echoes even from the deck on your vessel.

FISH SIZE

0

MENU/ESC


ENTER

RANGE


MARK

FUNC

HODE



ACCU-FISH™ OFF



ACCU-FISH™ ON

ACCU-FISH

ACCU-FISH[™] identifies individual fish with size and fish mark function

Recognizes individual or multiple fish instantaneously


ACCU-FISH[™] is a fish size assessment function of FCV-628 that is proprietary to FURUNO. In order to assess individual fish size, echo returns are evaluated based on strength and turned into fish size display on screen.

ACCU-FISH[™] can detect fish size from 10 to 199 cm, in depths of 2 to 100 m.

Display fish marks

The fish mark can be utilized to display individual fish echoes when they are detected. It helps beginners to identify fish echoes for a more engaging fishing experience. Fish marks are selectable from either a circle or square, as well as, two fish symbols. The fish symbols, displayed in two different sizes (Large: over 50 cm, Small: 10 to 49 cm), are a great help for anglers when identifying individual fish. The circle and square symbols identify individual fish without hiding the underlying echo.

In some instances, fish size indicated on FCV-628 may differ from actual size. Please read the operator's manual carefully before using this feature.



Circles displayed over fish echoes along with their approximate size.

technology, providing an incredible boos a compact narrowband transducer



Dual-frequency fish finder equipped with revolutionary new RezBoost[™] signal processing technology

Improved clarity and resolution that was previously impossible with conventional narrowband transducers has been made possible thanks to the new RezBoost™ technology.

► ACCU-FISH[™] - A unique fish size analyzer based on the latest digital technology



Bottom Discrimination - Analyze bottom structure

Provides an at-a-glance recognition of bottom composition with four types of graphical displays (Rocks/Sand/Gravel/Mud) when connected to a supported thru-hull or transom mount transducer.

White Line feature - Discriminate fish lying near the bottom

The top edge of the bottom echo is displayed in white to clearly show bottom structures. This feature helps to discriminate between weeds and bottom fish distinctly.

Configurable Alarm function (depth, fish echoes, etc.)

Share and display information on a chart plotter*

FURUNO's TLL (Target Lat/Lon) output allows you to interface the FCV-628 with your FURUNO chart plotter so that you can mark fishing grounds with various information (L/L, Depth, Water Temp, Fish size and Bottom type).


Fast transmission rate of 3,000 PRR (Pulse Repetition Rate) per minute (at 5 m depth range)

Bottom Discrimination function

FCV-628's Bottom Discrimination function enables the fish finder to indicate whether the bottom is composed mainly of rocks, gravel, sand or mud. The Bottom Discrimination function provides you with valuable information that helps you locate rich fishing grounds, and boost your catch of the day.

Please keep the following in mind when using the Bottom Discrimination Sounder:


- 1) Use at a depth of 5 m 100 m.
- 2) Use a transom or thru-hull mount transducer.
- 3) Install the transducer parallel to the bottom of the vessel.
- 4) To show a consistent display of the actual bottom, set the display range to "auto".
- 5) Enter the ship's draft value.
- 6) Use a ship speed of 10 kn or less.
- 7) In some instances, the bottom component indicated on the FCV-628 may differ from the actual bottom structure.
 - Please read the operator's manual carefully before using this feature.





Graphic mode

The standard graphic display mode shows the most probable bottom composition by graphic or four colors.



Probability mode The probability display mode shows the most probable

bottom composition in graph form.

White Line function distinguishes fish from the seabed

This function is useful for discriminating bottom fish as well as judging fish school density.




Fish Alarm function

When fish echoes appear in an area preset by the user, the FCV-628 will sound a loud alarm, as well as, display an alarm icon on screen. The integrated alarm can also be set to be triggered by specific conditions for water depth, target depth, water temperature, bottom type and more. You never have to miss a target again.



Swivel mounting bracket

The gimbal mount allows the display unit to swivel around when desktop mounted. You can adjust the angle of the display for optimal viewing comfort.



SPECIFICATIONS OF FCV-628

GENERAL

Frequency Output Power **DISPLAY**

Display Type Effective Display Area Pixel Number Display

Basic Range

Alarm

Language

Range Phasing Expansion Range

Picture Advance Speed

600 W

50 and 200 kHz

5.7" color LCD 87.1 (W) x 116.2 (H) mm 480 x 640 (VGA) Single frequency (50 or 200 kHz), Dual-frequency, Zoom, Nav data, A-scope, Marker zoom, Bottom zoom, Bottom-lock, Bottom Discrimination, ACCU-FISH™, RezBoost™ 2-1200 m* *m, ft, fm, HR, pb can be selected in the menu Bottom, Fish (Normal), ACCU-FISH™, Fish (B/L), Bottom Discrimination, Fish Level, Temperature, Speed, Arrival and Battery English, French, Spanish, German, Italian, Portuguese, Greek, Polish, Danish, Swedish, Norwegian, Finnish, Chinese, Japanese, Thai, Vietnamese up to 1200 m Bottom-lock expansion: 2-10 m Sectional expansion: 2-1200 m 8 steps: stop, 1/16, 1/8, 1/4, 1/2,

1, 2, 4 Pulselength & PRR Interface (IEC61162-1, NMEA 0183 Ver 1.0/2.0/3.0) Input: BWC, GGA, GLL, GNS, HDG, HDT, MDA, MTW, MWV, RMA, RMB, RMC, VHW, VTG, XTE, ZDA

Output: DBS, DBT, DPT, MTW*, RMB*, VHW*, TLL* by key operation * External data required

ENVIRONMENT

-15°C to +55°C IP56

12-24 VDC: 1.1-0.5 A

Waterproofing POWER SUPPLY

Temperature

EQUIPMENT LIST

Standard

1. Display Unit CV-628

- 2. Installation Materials and Standard Spare Parts **Option**
- 1. Speed/Temperature Sensor ST-02MSB, ST-02PSB, T-04MSB, T-04MTB
- 2. Connector Kit for Connection of Speed
- & Temperature Sensor or Temperature Sensor
- 3. NMEA+Power Cable

Алматы (7273)495-231 Ангарск (3955)60-70-56 Архангельск (8182)63-90-72 Астрахань (8512)99-46-04 Барнаул (3852)73-04-60 Белгород (4722)40-23-64 Благовещенск (4162)22-76-07 Брянск (4832)59-03-52 Владивосток (423)249-28-31 Владикавказ (8672)249-28-31 Владикавказ (8672)249-43-18 Волгоград (844)278-03-48 Волгоград (8172)26-41-59 Воронеж (473)204-51-73 Екатеринбург (343)384-55-89 Иваново (4932)77-34-06 Ижевск (3412)26-03-58 Иркутск (395)279-98-46 Казань (843)206-01-48 Калининград (4012)72-03-81 Калуга (4842)92-23-67 Кемерово (3842)95-04-62 Киров (8332)68-02-04 Коломна (4966)23-41-49 Кострома (4966)23-41-49 Кострома (4966)23-41-49 Кострома (4966)23-41-49 Краснордск (391)204-63-61 Курск (4712)77-13-04 Курган (3522)50-90-47 Липецк (4742)52-20-81

Россия +7(495)268-04-70

Магнитогорск (3519)55-03-13 Москва (495)268-04-70 Мурманск (8152)59-64-93 Набережные Челны (8552)20-53-41 Нижний Новгород (831)429-08-12 Ноябрьск (3496)41-32-12 Нояборск (3496)41-32-12 Новосибирск (383)227-86-73 Омск (3812)21-46-40 Ореп (4862)44-53-42 Оренбург (3522)37-68-04 Пенза (8412)22-31-16 Петроааводск (8142)55-98-37 Псков (8112)59-10-37 Пермь (342)205-81-47


Казахстан +7(7172)727-132


Transducers (Specify when ordering)

520-5PSD, 520-5MSD, 520-PLD, 525-5PWD, 525T-PWD, 525T-BSD, 525T-LTD/12, 525T-LTD/20, 525STID-MSD, 525STID-PWD, SS60-SLTD/12, SS60-SLTD/20


DISPLAY UNIT

Bracket Mount 1.3 kg 2.9 lb






Flush Mount 0.9 kg 2 lb



INTERCONNECTION DIAGRAM



Ростов-на-Дону (863)308-18-15 Рязань (4912)46-61-64 Самара (846)206-03-16 Санкт-Петербург (812)309-46-40 Саратов (845)249-38-78 Севастополь (8692)22-31-93 Саранск (8342)22-96-24 Симферополь (3652)67-13-56 Смоленск (4812)29-41-54 Сочи (862)225-72-31 Ставрополь (8652)20-65-13 Сургут (3462)77-98-35 Сыктывкар (8212)25-95-17 Тамбов (4752)50-40-97 Тверь (4822)63-31-35 Тольятти (8482)63-91-07 Томск (3822)98-41-53 Тула (4872)33-79-87 Тюмень (3452)66-21-18 Ульяновск (8422)24-23-59 Улан-Удэ (3012)59-97-51 Уда (347)229-48-12 Хабаровск (4212)92-98-04 Чебоксары (8352)28-53-07 Челябинск (351)202-03-61 Череповец (8202)49-02-64 Чита (3022)38-34-83 Якутск (4112)23-90-97 Яроспавль (4852)69-52-93

Киргизия +996(312)96-26-47

https://furuno.nt-rt.ru || fon@nt-rt.ru